HN-3040

Technical Data Sheet

Waterproofing polymer emulsion / HN-3040 is used for single component waterproof paint. / TDS

01 Product Description

Excellent flexibility, high elasticity, good water resistance, good weather resistance, good adhesion, maintaining long-term effective elasticity and waterproof ability, and having extremely strong adhesion to the substrate.

02 Key Benefits

- Excellent flexibility, high elasticity, good water resistance, good weather resistance, good adhesion, maintaining long-term effective elasticity and waterproof ability, and having extremely strong adhesion to the substrate.

03 Recommended Applications

- HN-3040 is used for single component waterproof paint.

04 Technical Data

Item	Specification
Appearance	Light blue liquid
Solid content	50±1%
Viscosity (25C)	1500-3000cps
pH	6.0-8.0
Minimum Film-forming Temperature (MFT)	0°C
Ca2+ stability	Pass

05 Compatibility

Compatible with most chemicals used in water-based paints.

06 Packaging, Storage and Transportation

- Packing: 50kgs plastic drum/160kgs plastic drum/200kgs plastic drum/1000kgs IBC pallet/20000kgs soft packing.

Safety: The water-based polymer emulsion is non-toxic and non-flammable. If it splashes into the eyes, it should be washed with plenty of water immediately.