HN-332T

Technical Data Sheet

Waterproofing polymer emulsion / HN-332T is used for elastic waterproof, 2-part cement based waterproof, putties, etc. / TDS

01 Product Description

Excellent cement compatibility, excellent low temperature performance, extensibility and tensile strength, excellent water, alkali and weather resistance.

02 Key Benefits

- Excellent cement compatibility, excellent low temperature performance, extensibility and tensile strength, excellent water, alkali and weather resistance.

03 Recommended Applications

- HN-332T is used for elastic waterproof, 2-part cement based waterproof, putties, etc.

04 Technical Data

Item	Specification
Appearance	Milky white liquid with a hint of green
Solid content	56±1wt%
Viscosity.cps(25℃)	1000-3000
pH	7.0-8.0
Glass Transition Temperature (Tg)	-31℃
Minimum Film Formation Temperature (MFT)	0℃

05 Compatibility

Compatible with most chemicals used in water-based paints.

06 Packaging, Storage and Transportation

- Packing: 50kgs plastic drum/160kgs plastic drum/200kgs plastic drum/1000kgs IBC pallet/20000kgs soft packing.

Safety: The water-based polymer emulsion is non-toxic and non-flammable. If it splashes into the eyes, it should be washed with plenty of water immediately.