HN-5025

Technical Data Sheet

Waterproofing polymer emulsion / HN-5025 is used for water-based non-cure rubber asphalt waterproof coatings, etc. / TDS

01 Product Description

Direct spraying construction is convenient without heating, waterproof coating is dense, strong bonding force, can be well bonded to the base and various coil. Excellent extensibility and self-healing characteristics.

02 Key Benefits

- Direct spraying construction is convenient without heating, waterproof coating is dense, strong bonding force, can be well bonded to the base and various coil.
- Excellent extensibility and self-healing characteristics.

03 Recommended Applications

- HN-5025 is used for water-based non-cure rubber asphalt waterproof coatings, etc.

04 Technical Data

Item	Specification
Appearance	Milky white liquid
Solid content	50±1%
Viscosity (25C)	500-2000cps
pH	6.5-7.5
Minimum Film-forming Temperature (MFT)	0°C

05 Compatibility

Compatible with most chemicals used in water-based paints.

06 Packaging, Storage and Transportation

- Packing: 50kgs plastic drum/160kgs plastic drum/200kgs plastic drum/1000kgs IBC pallet/20000kgs soft packing.

Safety: The water-based polymer emulsion is non-toxic and non-flammable. If it splashes into the eyes, it should be washed with plenty of water immediately.