HN-9105F

Technical Data Sheet

Styrene-acrylic copolymer emulsion / HN-9105F is used for transparent waterproof adhesives. / TDS

01 Product Description

Silicone modified styrene-acrylic emulsion, core-shell structure, good transparency, good weather resistance, high water resistance, anti-whiteness, strong adhesion, good adhesion to the substrate, fast drying, good film formation, excellent early water resistance.

02 Key Benefits

- Silicone modified styrene-acrylic emulsion, core-shell structure, good transparency, good weather resistance, high water resistance, anti-whiteness, strong adhesion, good adhesion to the substrate, fast drying, good film formation, excellent early water resistance.

03 Recommended Applications

- HN-9105F is used for transparent waterproof adhesives.

04 Technical Data

Item	Specification
Appearance	light blue liquid
Solid content	43±1%
Viscosity (25C)	2000-8000cps
pH	7.0-8.0
Minimum Film-forming Temperature (MFT)	0°C

05 Compatibility

Compatible with most chemicals used in water-based paints.

06 Packaging, Storage and Transportation

- Packing: 50kgs plastic drum/160kgs plastic drum/200kgs plastic drum/1000kgs IBC pallet/20000kgs soft packing.

Safety: The water-based polymer emulsion is non-toxic and non-flammable. If it splashes into the eyes, it should be washed with plenty of water immediately.